

Technical Specifications

Extra Heavy Duty – Drier/Scraper

Construction:	Tufted loop
Face Fibre:	75% recycled nylon – Econyl 75 (75% post-industrial, 5% post-consumer) 25% polypropylene
Dye Method:	Solution-dyed
Gauge:	7/32
Stitches per Inch:	8.33 (32.80 per 10cm)
Overall Thickness:	0.31" (7.9mm)
Tufted Yarn Weight:	26.2 oz/square foot (7.99 kg/square metre)
Pattern Repeat:	N/A
Primary Substrate:	100% Synthetic
Secondary Backing:	50% post-industrial recycled vinyl, 60 mil thickness
Installation Methods:	Loose-lay or direct glue-down using water-based vinyl-compatible adhesive
Methenamine Pill Test (ASTM-D-2859)	Passes
Flooring Radiant Panel Test (ASTM-E-648)	Class (Direct Glue)
N.B.S. Smoke Chamber Test (ASTM-E-662)	< 450 (flaming mode)
Electrostatic Propensity Test (AATCC 134)	< 2.0 KV
Available Widths	3' (0.91 metre) cuts, 6' (1.83 metre) cuts and rolls

The Grizzly FX entrance matting system meets the requirements of IEQ Credit 5: Indoor Chemical and Pollutant Source Control, outlined in the USF BC's LEED NC & CI Rating Systems.